

BK RUF N TUF - Технические спецификации



Description

BK RUF N TUF - шины с блочным рисунком протектора для эксплуатации на прицепах и легких грузовиках. Они идеально подходят для движения по дороге и обладают исключительной долговечностью.

UM

International Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Малотоннажный грузовик • Прицеп

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	8
Section Width (mm)	216
Overall Diameter (mm)	830
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	4.15
100 LS	1120
100 LD	975

Printed on 26.02.2024 2:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..