

COLT - Технические спецификации



Description

СОLТ - шины с блочным рисунком протектора для прицепов и легких грузовиков, используемых для перевозок как по дороге, так и по полям. Прочность и другие характеристики шин СОLТ остаются на высоком уровне на всем протяжении срока эксплуатации.

UM

International Standard

Construction



Machinery

Сельское хозяйство: Малотоннажный грузовик • Прицеп

Производство: Прицеп

Version	STANDARD
Туре	TT
Tyre Size	7.50 - 15

Dimensions International Standard

Ply Rating	12
Section Width (mm)	217
Overall Diameter (mm)	790
Rim Rec	6.00
ECE	E4-54R-0024094

Load capacity (Kg)

km/h / bar	6.00
100 LS	1385
100 LD	1315

Printed on 26.04.2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..