

COMMANDER 3 RIB - Технические спецификации



Description

COMMANDER 3 RIB — это передние шины с трехреберным рисунком протектора, разработанные для обработки почвы и грузоперевозок. Благодаря оптимизированному распределению нагрузки на ребра в центре и на боковинах они обеспечивают превосходную прочность и грузоподъемность. Прочный каркас и протектор из устойчивой к порезам и разрывам резиновой смеси гарантирует невероятную стойкость к проколам.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор 2WD

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	91 A8

Dimensions US Standard

Usa code	94046911
Ply Rating	8
Section Width (inch)	6.9
Overall Diameter (inch)	29.1
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004415
TRA Code	F2

Load capacity (lbs)

mph / psi	68
25	1360

Printed on 26.04.2024 10:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..