

## COMMANDER (F) - Технические спецификации



### Description

COMMANDER (F) — это передние шины с трехреберным рисунком протектора, которые отлично подходят для обработки почвы и грузоперевозок. Глубокий рисунок протектора на основе стойкой к порезам и разрывам резиновой смеси позволяет гарантировать долгий срок службы шин и высокую грузоподъемность.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	102 A6

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>TKPH</b>	1
<b>Section Width (mm)</b>	183
<b>Overall Diameter (mm)</b>	770
<b>Static Loaded Radius (mm)</b>	362
<b>Rolling Circumference (mm)</b>	2332
<b>Rim Rec</b>	4.50 E
<b>Rim Alt</b>	4.00 E ; 5.00 F ; 5.50 F
<b>ECE</b>	E11-106R-004109
<b>TRA Code</b>	F2

## Load capacity (Kg)

	km/h / bar	5.00
	30	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14.02.2025 16:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..