# CON STAR - Технические спецификации

## Description

Шины CON STAR особенно хорошо подходят для телескопических и компактных погрузчиков, используемых при проведении агропромышленных, подъемных и погрузочных работ. Они отличаются превосходной тягой наряду с потрясающей вертикальной и горизонтальной устойчивостью. Протектор CON STAR изготовлен из резиновой смеси, стойкой к порезам и разрывам, что гарантирует долгий срок службы этих шин.

## UM

International Standard

## Construction

BIAS

## Machinery

Сельское хозяйство: Компактный погрузчик • Телескопический погрузчик
Производство: компактный погрузчик • Телескопический погрузчик

| | |
|---|---|
| **Version** | INDUSTRIAL |
| **Type** | TL |
| **Tyre Size** | 340/80 - 20<br>(12.5/80 - 20) |
| **LI/SS** | 144 A8 |

## Dimensions International Standard

| | |
|---|---|
| **Section Width (mm)** | 350 |
| **Overall Diameter (mm)** | 1065 |
| **Static Loaded Radius (mm)** | 491 |
| **Rolling Circumference (mm)** | 3272 |
| **SRI (mm)** | 500 |
| **Rim Rec** | 11 |
| **Rim Alt** | 12 ; 11 SDC ; 12 SDC ; W 10 ; W 11 |
| **ECE** | E11-106R-003021 |

## Load capacity (Kg)

| km/h / bar | 4.00 |
|---|---|
| **40** | 2800 |

Printed on 06.05.2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..