

## CON STAR - Технические спецификации



### Description

Шины CON STAR особенно хорошо подходят для телескопических и компактных погрузчиков, используемых при проведении агропромышленных, подъемных и погрузочных работ. Они отличаются превосходной тягой наряду с потрясающей вертикальной и горизонтальной устойчивостью. Протектор CON STAR изготовлен из резиновой смеси, стойкой к порезам и разрывам, что гарантирует долгий срок службы этих шин.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Компактный погрузчик •

Телескопический погрузчик

Производство: компактный погрузчик • Телескопический погрузчик

Version	INDUSTRIAL
Type	TL
Tyre Size	460/70 - 24 (17.5L - 24)
LI/SS	159 A8

## Dimensions US Standard

Usa code	94052424
Section Width (inch)	18.1
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	22.1
Rolling Circumference (inch)	149
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E11-106R-003029

## Load capacity (lbs)

mph / psi	58
25	9650

Printed on 26.04.2024 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..