

## CRANE SPECIAL - Технические спецификации



### Description

Шины CRANE SPECIAL подходят для подъемных кранов, работающих на неровном грунте. Протекторы шин изготавливаются из специальной резиновой смеси, которая гарантирует хорошую устойчивость и прочность.

### UM

International Standard

### Construction

 BIAS

### Machinery

Производство: Самоходный кран

Version	STANDARD
Type	TT
Tyre Size	16.00 - 25

## Dimensions International Standard

<b>Ply Rating</b>	28
<b>Overall Width (mm)</b>	463
<b>Overall Diameter (mm)</b>	1485
<b>Static Loaded Radius (mm)</b>	682
<b>Rolling Circumference (mm)</b>	4395
<b>Rim Rec</b>	11.25/2.0
<b>TRA Code</b>	E3

## Load capacity (Kg)

km/h / bar	5.75
50	6700

Printed on 06.12.2023 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..