

# EARTHMAX CRUSHER HAUL - Технические спецификации



## Description

EARTHMAX CRUSHER HAUL — это радиальная шина со стальным брекером, разработанная для транспортных перевозок как на дороге, так и в условиях бездорожья, и на горнодобывающих предприятиях. Стальной брекер и усиленный каркас шины обеспечивают увеличенный срок службы и повышенную ходимость в сочетании с высокой несущей способностью. Благодаря рисунку протектора из крупных блоков шина обладает отличными тяговыми свойствами. С шиной EARTHMAX CRUSHER HAUL водитель устает куда меньше, а превосходный ходовой комфорт и отличная управляемость гарантированы.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Производство: Дорожный/внедорожный грузовик

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	149/146 J

## Dimensions International Standard

Ply Rating	18
Overall Width (mm)	272
Overall Diameter (mm)	1065
Rim Rec	7.50
Rim Alt	8.00

## Load capacity (Kg)

	km/h / bar	8.30
	100 Load Single	3250
	100 Load Dual	3000

Printed on 25.04.2024 20:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..