

EARTHMAX SR 23 - Технические спецификации



Description

EARTHMAX SR 23 (G-2/L-2) - это радиальная шина с цельным металлокордом, специально разработанная для автогрейдеров и погрузчиков. Она отличается превосходными тяговыми характеристиками в продольном и поперечном направлениях и улучшенной способностью к самоочищению. Своим долгим сроком службы эта шина обязана прочному каркасу и невероятно стойкому к порезам протектору.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Грейдер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	153 A8/176 A2

Dimensions International Standard

Overall Width (mm)	448
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	612
Rolling Circumference (mm)	4108
Rim Rec	14.00/1.5
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1850	2120	2360	2650	2900	3075	3350	3650	-	-	-	-	-
10	-	-	-	-	-	-	-	-	6000	6150	6500	6700	7100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.12.2024 11:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..