

EARTHMAX SR 25 PLUS - Технические спецификации



Description

EARTHMAX SR 25 PLUS (G-2/L-2) - это радиальные шины с **цельным металлокордом**, которые изготовлены специально для автогрейдеров и погрузчиков, работающих в самых сложных условиях при строительстве дорог или на горных разработках. Ненаправленный рисунок их протектора гарантирует превосходную самоочистительную способность в дополнение к тяговым характеристикам и устойчивости при движении по бездорожью.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Бульдозер • Грейдер • Погрузчик
Производство: Бульдозер • Грейдер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

Dimensions International Standard

Overall Width (mm)	359
Overall Diameter (mm)	1372
Static Loaded Radius (mm)	626
Rolling Circumference (mm)	4146
Rim Rec	8.00TG
Rim Alt	9.00GR
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Printed on 21.04.2024 23:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..