

EARTHMAX SR 30 - Технические спецификации



Description

EARTHMAX SR 30 (E-3/L-3) - радиальные шины двойного назначения с цельным металлокордом для погрузчиков и самосвалов с шарнирно-сочлененной рамой. Многослойный металлокордный брекер и твердый протектор с блочным рисунком обеспечивают великолепные тяговые характеристики, устойчивость и долговечность шин. За счет использования специальной стойкой к порезам резиновой смеси, шины EARTHMAX SR 30 станут идеальным решением для эксплуатации в самых жестких условиях.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Шарнирно-сочлененный самосвал •
Бульдозер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

Dimensions US Standard

Usa code	94054459
TMPH	158
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400

Printed on 26.04.2024 15:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..