

## EARTHMAX SR 313 - Загрузить лист технических данных



### Description

EARTHMAX SR 313 is an All Steel radial tire specifically designed for Articulated Dump Trucks and Loaders operating in hard rocky conditions. Its cut resistant compound and special tread design allow for protection against cuts and damages, together with self-cleaning properties. Its square shoulder design maximizes ground contact for excellent maneuverability. The All Steel radial construction with multi-layer steel belts ensures extra durability. EARTHMAX SR 313 is the ideal tire for hauling and load-and-carry operations.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: Шарнирно-сочлененный самосвал •  
Погрузчик

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
15.5 R 25	CUT RESISTANT COMPOUND	94066964	E3/L3	**/*	160 B/169 A2	12.00/1.3		15.5	49.8	22.3	150.5	TL	92

Printed on 21.04.2024 23:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..