

EARTHMAX SR 315 - Технические спецификации



Description

EARTHMAX SR 315 — это радиальные шины с цельным металлокордом, специально разработанные для погрузочно-доставочных машин. Модель превосходно себя зарекомендовала при выемке породы, а также при выполнении погрузочно-транспортных работах в условиях горных выработок.

Своими характеристиками шины обязаны прочному каркасу, усиленному несколькими стальными брекерными слоями, минимизирующими риски проколов при наезде на острые камни, а также от ударных нагрузок. Армированные боковины и плечевые зоны EARTHMAX SR 315 гарантируют превосходные эксплуатационные показатели в условиях применения на каменистых поверхностях, снижая риски порезов и абразивных повреждений боковин о камни. Гладкий рисунок протектора L-3S способствует уменьшению количества застревающих в нем камней. Специально разработанная для модели EARTHMAX SR 315 резиновая смесь уменьшает нагрев шины во время движения и обеспечивает ее надежность при эксплуатации в подземных условиях

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Погрузочно-доставочная машина

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 29
LI/SS	211 A2

Dimensions International Standard

Overall Width (mm)	725
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5635
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L3S

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	16500	17500	18000	18500	19000	19500

Printed on 20.04.2024 17:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..