

EARTHMAX SR 315 - Загрузить лист технических данных



Description

EARTHMAX SR 315 — это радиальные шины с цельным металлокордом, специально разработанные для погрузочно-доставочных машин. Модель превосходно себя зарекомендовала при выемке породы, а также при выполнении погрузочно-транспортных работах в условиях горных выработок.

Своими характеристиками шины обязаны прочному каркасу, усиленному несколькими стальными брекерными слоями, минимизирующими риски проколов при наезде на острые камни, а также от ударных нагрузок. Армированные боковины и плечевые зоны EARTHMAX SR 315 гарантируют превосходные эксплуатационные показатели в условиях применения на каменистых поверхностях, снижая риски порезов и абразивных повреждений боковин о камни. Гладкий рисунок протектора L-3S способствует уменьшению количества застревающих в нем камней. Специально разработанная для модели EARTHMAX SR 315 резиновая смесь уменьшает нагрев шины во время движения и обеспечивает ее надежность при эксплуатации в подземных условиях

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Погрузочно-доставочная машина

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 29	CUT RESISTANT COMPOUND	94067411	L3S	**	211 A2	22.00/3.0		28.5	73.4	32.7	221.9	TL
26.5 R 29	CUT RESISTANT COMPOUND	94070787	L3S	***	217 A2	22.00/3.0		28.5	73.4	32.7	221.9	TL

Printed on 23.04.2024 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..