

EARTHMAX SR 31 - Технические спецификации



Description

EARTHMAX SR 31 - это радиальная шина с цельным металлокордом, специально разработанная для самосвалов с шарнирно-сочлененной рамой и колесных погрузчиков. Залогом прочности и устойчивости этой шины выступают большое количество брекерных слоев с металлокордом, а множество разнонаправленных жестких блоков протектора гарантирует им превосходные тяговые характеристики и маневренность даже на грязи. Помимо выдающегося ходового комфорта, шина EARTHMAX SR 31 отличается специальной резиновой смесью протектора, которая наделена исключительной стойкостью к порезам и теплообразованию. Она гарантирует отличный комфорт при выполнении погрузочно-транспортных операций на твердых подготовленных поверхностях. Радиальная конструкция способствует снижению сопротивления качению, что положительно сказывается на топливной экономичности транспортных средств.

UM

US Standard

Construction



RADIAL

Machinery

Производство: Бульдозер • Погрузчик

Производство: Шарнирно-сочлененный самосвал •
Бульдозер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions US Standard

Usa code	94060610
TMPH	116
Overall Width (inch)	21.3
Overall Diameter (inch)	58.3
Static Loaded Radius (inch)	26.1
Rolling Circumference (inch)	175.2
Rim Rec	17.00/2.0
Rim Alt	--
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	40

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	12800	13600	14300	14800	15200	16100
5	17600	18200	19300	19800	20900	--

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13.05.2025 15:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..