EARTHMAX SR 33 - Загрузить лист технических данных

Description

Earthmax SR 33 - это радиальные шины для грузовиков широкого профиля. Много-блочный рисунок их протектора разработан специально, чтобы обеспечить невероятные тяговые характеристики на мягких, песчаных или илистых грунтах. Помимо исключительных свойств самоочищения, шины Earthmax SR 33 демонстрируют превосходную устойчивость. Прочный цельнометаллический каркас отличается потрясающей прочностью и стойкостью к повреждениям и проколам.

UM

International Standard

Construction

RADIAL

Machinery

Производство: Универсальный автомобиль

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
14.00 R 20	STANDARD	164/160 J	10.0	9.0, 10.00W	390	1250	576	3840	TL	E11-54R-0016678
335/80 R 20	STANDARD	150 K	11		335	1047	464	3145	TL	E11-54R-0016679
365/80 R 20 (14.5 R 20)	STANDARD	152 K	11		360	1096	496	3318	TL	E11-54R-0017314
395/85 R 20	STANDARD	168 J	10.00W	10.00HF	394	1184	538	3589	TL	E11-54R-0017315

Printed on 19.04.2024 8:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..