

EARTHMAX SR 41 - Технические спецификации



Description

EARTHMAX SR 41 (E-4/L-4) — это радиальная шина со стальным кордом, идеально подходящая для шарнирно-сочлененных самосвалов, погрузчиков и бульдозеров. Полностью стальная конструкция и специальный рисунок протектора шины EARTHMAX SR 41 обеспечивают превосходную стойкость к проколам и повышенный срок службы. Шина EARTHMAX SR 41 также предлагается в варианте E4**** для низкопрофильных самосвалов, используемых для подземных транспортировочных работ.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Шарнирно-сочлененный самосвал •
Бульдозер • Погрузчик • Низкопрофильный самосвал

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	35/65 R 33

Dimensions US Standard

Usa code	94069415
Overall Width (inch)	35.3
Overall Diameter (inch)	81.2
Static Loaded Radius (inch)	36.5
Rolling Circumference (inch)	247.4
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

Load capacity (lbs)

mph / psi

* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 25.04.2024 19:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..