EARTHMAX SR 423 - Загрузить лист технических данных

Description

EARTHMAX SR 423 — это радиальные шины с цельным металлокордом для техники, используемой при выполнении различных видов работ, включая разработку карьеров, перевозку грузов и транспортировку леса. Ненаправленный рисунок протектора обеспечивает превосходную тягу и устойчивость на любом покрытии. Шина идеальна для работы с тяжелыми грузами. Прочный цельнометаллический каркас отличается превосходной надежностью и стойкостью к повреждениям и проколам. Усиленный борт и рисунок плечевой зоны повышают срок службы шины даже в сложных условиях эксплуатации.

UM

US Standard

Construction

RADIAL

Machinery

Производство: Дорожный/внедорожный грузовик

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type
10.00 R 20	STANDARD	94060481	149/146 J	7.50	8.00	10.6	41.9	TT
11.00 R 20	STANDARD	94060672	152/149 J	8.00	8.50	11.2	43.3	TT
12.00 R 20	STANDARD	94062805	154/150 J	8.50	9.00	11.9	44.6	TT
12.00 R 24 (325/95 R 24)	STANDARD	94062096	160/156 K	8.50		12.5	48.9	TT
325/95 R 24 (12.00 R 24)	STANDARD	94063727	160/156 K	8.50		12.5	48.9	TT

Printed on 26.04.2024 5:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..