

EARTHMAX SR 431 - Технические спецификации



Description

EARTHMAX SR 431 (E-4) — это радиальная шина с цельным металлокордом, которая спроектирована специально для жесткорамных самосвалов, работающих в самых сложных условиях горных разработок (наземные и подземные работы). Ненаправленный рисунок протектора гарантирует превосходную тягу и устойчивость. Прочный цельнометаллический каркас и специальная резиновая смесь протектора шины обеспечивают отличную стойкость к проколам и порезам, а также долгий срок службы даже на каменистых, неровных и жестких поверхностях. .

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 18.00 R 25 |
| LI/SS | 185 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94060788 |
| TMPH | 96 |
| Overall Width (inch) | 20.5 |
| Overall Diameter (inch) | 65.4 |
| Static Loaded Radius (inch) | 29.9 |
| Rolling Circumference (inch) | 198.4 |
| Rim Rec | 13.00/2.5 |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| | | | | | | | | | |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
| 30 | 16100 | 16500 | 17100 | 17600 | 18200 | 18700 | 19300 | 19800 | 20400 |

Printed on 20.04.2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..