

## EARTHMAX SR 43 - Технические спецификации



### Description

EARTHMAX SR 43 (L-4) — это радиальная шина с цельным металлокордом, которая спроектирована специально для колесных погрузчиков, работающих в самых сложных условиях горных разработок, в основном подземных. Она демонстрирует образцовые характеристики при выполнении операций погрузки и транспортировки в карьерах, шахтах и на свалках. Отличительными качествами уникального рисунка протектора выступают великолепные тяговые характеристики и устойчивость. Благодаря цельнометаллическому каркасу шина EARTHMAX SR 43 (L-4) обладает поразительной прочностью и великолепной стойкостью к сколам и проколам, а также имеет долгий срок службы.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Производство: Погрузчик

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 35/65 R 33             |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Overall Width (mm)         | 900       |
| Overall Diameter (mm)      | 2076      |
| Static Loaded Radius (mm)  | 957       |
| Rolling Circumference (mm) | 6412      |
| Rim Rec                    | 28.00/3.5 |
| Star Rating                | ****/***  |
| TRA Code                   | E4/L4     |

## Load capacity (Kg)

|            |   |
|------------|---|
| km/h / bar | - |
| -          | - |

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 27.04.2024 13:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..