

EARTHMAX SR 44 - Технические спецификации



Description

EARTHMAX SR 44 (E-4) - это радиальные шины с цельным металлокордом для техники, используемой при выполнении различных видов работ, включая горные работы, перевозку грузов и транспортировку леса. Массивный рисунок протектора E-4 обеспечивает как отличные тяговые характеристики, так и комфорт оператора машины. Шины EARTHMAX SR 44 (E-4) помогут оптимизировать продуктивность, независимо от вида выполняемых работ.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Дорожный/внедорожный грузовик

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	146/143 G

Dimensions US Standard

Usa code	94045075
Ply Rating	16
Overall Width (inch)	10.6
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	126
Rim Rec	7.50
Rim Alt	7.0 ; 7.50VM ; 8.0
ECE	E11-54R-0015908

Load capacity (lbs)

mph / psi	120
55	6600

Printed on 26.04.2024 7:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..