

EARTHMAX SR 45 PLUS - Технические спецификации



Description

EARTHMAX SR 45 PLUS - это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Они идеально подходят для перевозок на дальние расстояния. Рисунок протектора шин EARTHMAX SR 45 PLUS минимизирует вибрации и шум.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	540
Overall Width (mm)	746
Overall Diameter (mm)	2702
Static Loaded Radius (mm)	1214
Rolling Circumference (mm)	8095
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 19.04.2024 15:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..