

EARTHMAX SR 454 - Технические спецификации



Description

EARTHMAX SR 454 — это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Уникальный рисунок протектора E-3 и особая центральная канавка обеспечивают оптимизированное сцепление в поперечном направлении и управляемость на рыхлых и глинистых грунтах. Эта шина прекрасно подходит для высоких скоростей и участков с большим плечом откатки при невысоких рабочих температурах. Благодаря стальному каркасу и многослойному стальному брекеру гарантируется превосходная стойкость к ударам и проколам от камней, что позволяет сократить время простоев и повысить производительность. Благодаря прямоугольной плечевой зоне шины EARTHMAX SR 454 увеличивается пятно контакта с поверхностью. Это способствует отличной маневренности и курсовой устойчивости, а также помогает снизить уровень шума и вибрации.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions International Standard

TKPH	884
Overall Width (mm)	900
Overall Diameter (mm)	2990
Static Loaded Radius (mm)	1358
Rolling Circumference (mm)	9085
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	30000	30750	32500	33500	34500	35500	36500	37500	38750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08.12.2024 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..