EARTHMAX SR 45 - Технические спецификации

Description

EARTHMAX SR 45 - это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Шины EARTHMAX SR 45 идеально подходят для техники, которая используется при выполнении всех видов работ, требующих высоких тяговых характеристик.

UM

International Standard

Construction

RADIAL

Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	191 B

Dimensions International Standard

TKPH	220
Overall Width (mm)	505
Overall Diameter (mm)	1870
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5608
Rim Rec	13.00/2.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Printed on 27.04.2024 19:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..