

EARTHMAX SR 47 - Технические спецификации



Description

EARTHMAX SR 47 (E-4) - это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой, работающих в условиях, которые требуют максимальной стойкости к порезам от острых камней и проколам. Глубина протектора E-4 и его уникальный рисунок обеспечивают высокую износостойкость даже при перевозках на дальние расстояния, сокращая таким образом время простоя и повышая производительность техники. Доступны в стандартном исполнении и в версии с более высокой стойкостью к порезам.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

| | |
|-----------|-------------------|
| Version | STANDARD COMPOUND |
| Type | TL |
| Tyre Size | 18.00 R 33 |
| LI/SS | 191 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94046102 |
| TMPH | 140 |
| Overall Width (inch) | 20.1 |
| Overall Diameter (inch) | 74.2 |
| Static Loaded Radius (inch) | 34.1 |
| Rolling Circumference (inch) | 223.4 |
| Rim Rec | 13.00/2.5 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 18700 | 19300 | 19800 | 20400 | 21500 | 22000 | 22700 | 23400 | 24000 |

Printed on 13.04.2024 17:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..