

EARTHMAX SR 47 - Загрузить лист технических данных



Description

EARTHMAX SR 47 (E-4) - это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой, работающих в условиях, которые требуют максимальной стойкости к порезам от острых камней и проколам. Глубина протектора E-4 и его уникальный рисунок обеспечивают высокую износостойкость даже при перевозках на дальние расстояния, сокращая таким образом время простоя и повышая производительность техники. Доступны в стандартном исполнении и в версии с более высокой стойкостью к порезам.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94064489	E4	***	195 B	13.00/2.5		20.1	74.2	34.1	223.4	TL	115
18.00 R 33	CUT RESISTANT COMPOUND	94045815	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	115
18.00 R 33	HEAT RESISTANT	94070190	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	156
18.00 R 33	STANDARD COMPOUND	94064472	E4	***	195 B	13.00/2.5		20.1	74.2	34.1	223.4	TL	140
18.00 R 33	STANDARD COMPOUND	94046102	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	140
21.00 R 33	CUT RESISTANT COMPOUND	94057801	E4	**	200 B	15.00/3.0	--	22.6	78.8	36.1	240.7	TL	155
21.00 R 33	STANDARD COMPOUND	94057788	E4	**	200 B	15.00/3.0	--	22.6	78.8	36.1	240.7	TL	185
21.00 R 35	CUT RESISTANT COMPOUND	94064380	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	179
21.00 R 35	HEAT RESISTANT COMPOUND	94069842	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	243
21.00 R 35	STANDARD COMPOUND	94065288	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	209
24.00 R 35	CUT RESISTANT COMPOUND	94041244	E4	**	209 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	182
24.00 R 35	CUT RESISTANT COMPOUND	94060917	E4	***	212 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	182
24.00 R 35	STANDARD COMPOUND	94041251	E4	**	209 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	216
24.00 R 35	STANDARD COMPOUND	94060924	E4	***	212 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	216

Printed on 13.04.2024 17:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..