EARTHMAX SR 49 M - Технические спецификации

Description

EARTHMAX SR 49 M — это радиальная шина со специальным ненаправленным рисунком протектора, которая спроектирована для погрузочно-доставочных машин (LHD), погрузчиков и бульдозеров, работающих в самых сложных условиях горных разработок, в основном подземных. EARTHMAX SR 49 M идеально подходит для сложных операций, когда требуются исключительные тяговые характеристики и устойчивость. Глубокий рисунок протектора и специально разработанная резиновая смесь шины L-4 для работы в подземных шахтах обеспечивают более долгий срок службы протектора и выдающуюся устойчивость к порезам и проколам камнями.

UM

US Standard

Construction

RADIAL

Machinery

Производство: Бульдозер • Погрузочно-доставочная машина • Погрузчик • Низкопрофильный самосвал

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions US Standard

Usa code	94058969
Overall Width (inch)	27.9
Overall Diameter (inch)	70.2
Static Loaded Radius (inch)	31.5
Rolling Circumference (inch)	208.5
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L4

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	28300	29100	30900	32000	33100

Printed on 24.04.2024 0:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..