

EARTHMAX SR 50 - Загрузить лист технических данных



Description

EARTHMAX SR 50 (L-5) - это радиальные шины с цельным металлокордом, специально разработанные для погрузчиков. Надежный каркас и защита боковин предусмотрены специально для того, чтобы шины можно было использовать даже в самых сложных условиях. Шины EARTHMAX SR 50 изготовлены из специальной резиновой смеси, стойкой к порезам, что гарантирует долгий срок службы. Операторы также оценят их отличные тяговые характеристики, устойчивость и ходовой комфорт.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Погрузчик

| SIZE | Version | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|-----------|------------------------|----------|--------|--------|-----------|---------|-----|------|-----|------|------|
| 26.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 202 A2 | 22.00/3.0 | | 690 | 1772 | 806 | 5334 | TL |
| 26.5 R 25 | CUT RESISTANT COMPOUND | L5 | ** | 209 A2 | 22.00/3.0 | | 690 | 1772 | 806 | 5334 | TL |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 208 A2 | 25.00/3.5 | | 775 | 1901 | 862 | 5722 | TL |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L5 | ** | 216 A2 | 25.00/3.5 | | 775 | 1901 | 862 | 5722 | TL |

Printed on 24.04.2024 9:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..