

## EARTHMAX SR 51 - Технические спецификации



### Description

EARTHMAX SR 51 (L-5) - это радиальные шины с цельным металлокордом, специально разработанные для погрузчиков или бульдозеров. Шины EARTHMAX SR 51 идеально подойдут для техники, эксплуатируемой в суровых условиях, когда от шин требуется высокая устойчивость к порезам, защита боковин и исключительные тяговые характеристики.

### UM

International Standard

### Construction

RADIAL

### Machinery

Производство: Бульдозер, Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	211 A2

### Dimensions International Standard

Overall Width (mm)	777
Overall Diameter (mm)	1990
Static Loaded Radius (mm)	842
Rolling Circumference (mm)	5872
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5, 26.00/3.5
Star Rating	*
TRA Code	L5

### Load capacity (Kg)

km/h / bar	4.00	4.25	4.5	4.75	5.00
10	16500	17000	18000	18500	19500

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*