

EARTHMAX SR 51 - Технические спецификации



Description

EARTHMAX SR 51 (L-5) - это радиальные шины с цельным металлокордом, специально разработанные для погрузчиков или бульдозеров. Шины EARTHMAX SR 51 идеально подойдут для техники, эксплуатируемой в суровых условиях, когда от шин требуется высокая устойчивость к порезам, защита боковин и исключительные тяговые характеристики.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Бульдозер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	229 A2

Dimensions International Standard

Overall Width (mm)	905
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	872
Rolling Circumference (mm)	6082
Rim Rec	28.00/3.5
Star Rating	***
TRA Code	L5

Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	29000	30000	30750	31500	32000	32500

Printed on 24.04.2024 20:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..