

EARTHMAX SR 53 - Технические спецификации



Description

EARTHMAX SR 53 — это радиальная шина с цельным металлокордом, которая специально разработана для низкопрофильных самосвалов (LPDT) и погрузочно-доставочных машин (LHD), работающих в самых сложных условиях горных разработок, включая работы под землей, на шахтах и на свалках. Высокий рисунок протектора L-5 и стойкая к порезам резиновая смесь обеспечивают превосходные характеристики износостойкости, а также прекрасную тягу и устойчивость.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Бульдозер • Погрузчик • Низкопрофильный самосвал

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	182 A2

Dimensions US Standard

Usa code	94058945
Overall Width (inch)	17.1
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	165.9
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	16100	16500	17100	17600	18200	18700

Printed on 23.04.2024 12:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..