

## EARTHMAX SR 53 - Технические спецификации



### Description

EARTHMAX SR 53 — это радиальная шина с цельным металлокордом, которая специально разработана для низкопрофильных самосвалов (LPDT) и погрузочно-доставочных машин (LHD), работающих в самых сложных условиях горных разработок, включая работы под землей, на шахтах и на свалках. Высокий рисунок протектора L-5 и стойкая к порезам резиновая смесь обеспечивают превосходные характеристики износостойкости, а также прекрасную тягу и устойчивость.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: Бульдозер • Погрузчик • Низкопрофильный самосвал

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	188 A2

## Dimensions US Standard

Usa code	94064021
Overall Width (inch)	17.1
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	165.9
Rim Rec	14.00/1.5
Star Rating	***
TRA Code	L5

## Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	19300	19800	20400	20900	21500	22000

Printed on 23.04.2024 10:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..