EARTHMAX SR 55 - Технические спецификации

Description

EARTHMAX SR 55 — это радиальные шины с цельным металлокордом, которые изготовлены специально для погрузчиков, бульдозеров и низкопрофильных самосвалов, работающих в самых сложных условиях горных разработок и разработок карьеров. Благодаря отличной устойчивости к порезам за счет более глубокого и гладкого рисунка протектора шины EARTHMAX SR 55 помогут обеспечить наивысшую эффективность работы и сократить время простоя. При этом они очень прочные. Операторы также оценят превосходную устойчивость и тягу.

UM

US Standard

Construction

RADIAL

Machinery

Производство: Бульдозер • Погрузочно-доставочная машина • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	218 A2

Dimensions US Standard

Usa code	94040193
Overall Width (inch)	30.5
Overall Diameter (inch)	79.1
Static Loaded Radius (inch)	35.9
Rolling Circumference (inch)	238.1
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5, 26.00/3.5
Star Rating	**
TRA Code	L5S

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	44100	45400	46700	49400	50700	52000

Printed on 26.04.2024 4:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..