

# EARTHMAX SR LOADER - Загрузить лист технических данных



## Description

EARTHMAX SR LOADER — это внедорожная шина, специально разработанная для подъемно-разгрузочной и землеройной техники, а также шарнирно-сочлененных самосвалов. Металлокордный каркас, усиленный многослойным металлокордным брекерным поясом, и особая резиновая смесь протектора стали залогом исключительной стойкости к порезам и проколам, что увеличивает срок службы. Шина EARTHMAX SR LOADER обладает уникальным рисунком протектора с хорошими характеристиками самоочистки и отличным сцеплением на разнообразных дорожных покрытиях.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Производство: Шарнирно-сочлененный самосвал •  
Бульдозер • Погрузчик

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
20.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	177 B/186 A2	17.00/2.0		530	1475	649	4384	TL	170
23.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	185 B/195 A2	19.50/2.5	--	612	1605	706	4770	TL	200
26.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	193 B/202 A2	22.00/3.0		681	1735	763	5179	TL	230
29.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	200 B/208 A2	25.00/3.5		768	1859	818	5549	TL	270

Printed on 19.04.2024 4:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..