

EM 936 SUPER - Технические спецификации



Description

Шины EM 936 SUPER разработаны специально для экскаваторов и телескопических погрузчиков, выполняющих землеройные и погрузочные работы, а также транспортировку грузов. Увеличенная на 8–10 % ширина протектора шины EM 936 SUPER обеспечивает превосходную устойчивость и повышенный комфорт при движении. Они также гарантируют высокий уровень управляемости и превосходную тягу даже в условиях эксплуатации при больших нагрузках.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Экскаватор

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions US Standard

Usa code	94062690
Ply Rating	16
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	108
30	6600

Printed on 15.05.2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..