

## EM 937 (E3) - Технические спецификации



### Description

Шины EM 937 (E-3) разработаны специально для самосвалов с жесткой рамой, работающих в открытых карьерах. Они отличаются исключительной долговечностью и более высокой устойчивостью к порезам и разрывам. Шины EM 937 (E-3) особенно подходят для эксплуатации при больших нагрузках.

### UM

International Standard

### Construction

 BIAS

### Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

## Dimensions International Standard

<b>Ply Rating</b>	28
<b>Overall Width (mm)</b>	375
<b>Overall Diameter (mm)</b>	1368
<b>Static Loaded Radius (mm)</b>	620
<b>Rolling Circumference (mm)</b>	4105
<b>Rim Rec</b>	10.00/1.5
<b>TRA Code</b>	E3/L3

## Load capacity (Kg)

km/h / bar	6.50	9.25
50	5600	-
10	-	10000

Printed on 02.12.2023 12:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..