

F 240 - Технические спецификации



Description

F 240 - это шина, созданная для лесозаготовительных машин. Благодаря рисунку протектора она обеспечивает великолепную передачу тягового усилия, а также отличается превосходными свойствами самоочистки и отличной управляемостью. Выдающаяся резиновая смесь гарантирует ей невероятную стойкость к порезам и износу, что ведет к долгому сроку службы. Шина F 240 обращает на себя внимание большой площадью пятна контакта и, как следствие, улучшенной устойчивостью.

UM

US Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Трелевочный трактор

Version	STANDARD
Type	TT
Tyre Size	400 - 15.5 (400 - 15.5)

Dimensions US Standard

Usa code	94051588
Ply Rating	12
Section Width (inch)	15.9
Overall Diameter (inch)	34.1
Rim Rec	AG 13.00
ECE	E11-106R-004260
TRA Code	LS2

Load capacity (lbs)

mph / psi	55
20	6945

Printed on 28.04.2024 4:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..