

## FARM 2000 - Технические спецификации



### Description

Шины FARM 2000 предназначены для тракторов, используемых для обработки почвы. Шины изготавливаются из специальной резиновой смеси, устойчивой к порезам и разрывам, для обеспечения большей прочности. Благодаря крепкому каркасу шины FARM 2000 обладают высокой грузоподъемностью. Они также демонстрируют отличные тяговые характеристики и свойства самоочищения.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	128 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	345
Overall Diameter (mm)	1335
Static Loaded Radius (mm)	622
Rolling Circumference (mm)	4080
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003002
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	1800

Printed on 19.04.2024 22:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..