



# FARM HIGHWAY TOUGH - Технические спецификации



## Description

FARM HIGHWAY TOUGH — высокоскоростная шина для прицепов и сельскохозяйственной техники, которые используются для обработки почвы и грузовых перевозок. Шина обладает долгим сроком службы и обеспечивают повышенную грузоподъемность, в том числе и на высокой скорости.

## UM

International Standard

## Construction

 BIAS

## Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •  
Прицеп

Version	STANDARD
Type	TL
Tyre Size	11L - 15 FI
LI/SS	120 J

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	279
Overall Diameter (mm)	777
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2214
Rim Rec	8 LB
Rim Alt	10 LB ; 8 J
ECE	E11-54R-0018902

## Load capacity (Kg)

km/h / bar	4.10
100	1400

Printed on 26.04.2024 11:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..