



FARM HIGHWAY TOUGH - Технические спецификации



Description

FARM HIGHWAY TOUGH — высокоскоростная шина для прицепов и сельскохозяйственной техники, которые используются для обработки почвы и грузовых перевозок. Шина обладает долгим сроком службы и обеспечивают повышенную грузоподъемность, в том числе и на высокой скорости.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

Version	STANDARD
Type	TL
Tyre Size	12.5L - 15 FI
LI/SS	134 J

Dimensions International Standard

Ply Rating	12
Section Width (mm)	317
Overall Diameter (mm)	815
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2323
Rim Rec	10 LB
ECE	E11-54R-0019049

Load capacity (Kg)

km/h / bar	6.20
100	2120

Printed on 28.04.2024 22:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..