FL 252 - Технические спецификации

Description

Шины FL 252 подходят для роторных сенных граблей/ сеноворошилок, используемых для сеноуборочных работ, а также для вилочных погрузчиков, задействованных в логистических операциях. Эти шины обладают исключительной долговечностью, тогда как особый рисунок протектора обеспечивает максимальную устойчивость во время подъемных работ.

UM

US Standard

Construction

BIAS

Machinery

Сельское хозяйство: Роторные грабли / Сеноворошилка
Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions US Standard

Usa code	94006854
Ply Rating	10
Section Width (inch)	6.7
Overall Diameter (inch)	21.7
Rim Rec	4.00 E

Load capacity (lbs)

mph / psi	123
15 LOAD WHEEL	3780
15 STEER WHEEL	2910
5 OTHER VEHICLES	3780
15 OTHER VEHICLES	2910
STATIC SIDE LOADER	4400

Printed on 29.04.2024 6:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..