

## FL 630 SUPER - Технические спецификации



### Description

FL 630 SUPER — шины высокой проходимости для прицепов, цистерн и разбрасывателей, используемых для работы в поле и на дороге. Стойкая конструкция обеспечивает превосходную тягу и великолепное сцепление даже в поворотах и во время маневров. Усиленный борт и брекер из металлокорда гарантируют повышенную устойчивость.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Разбрасыватель • Автоцистерна •  
Прицеп

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D

## Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	549
Rolling Circumference (mm)	3785
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006945

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
70	1555	1745	2170	2465	2850	3230	3530	3870	4250	4750
65	1690	1900	2360	2685	3100	3515	3840	4210	4625	5150
50	2050	2300	2860	3250	3755	4260	4650	5100	5600	6235
40	2300	2580	3210	3650	4215	4785	5225	5725	6290	7005
25	2670	3000	3730	4240	4900	5560	6070	6655	7310	8140
10	3040	3415	4250	4830	5580	6330	6910	7580	8325	9270

Printed on 25.04.2024 23:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..