

## FL 630 SUPER - Технические спецификации



### Description

FL 630 SUPER — шины высокой проходимости для прицепов, цистерн и разбрасывателей, используемых для работы в поле и на дороге. Стойкая конструкция обеспечивает превосходную тягу и великолепное сцепление даже в поворотах и во время маневров. Усиленный борт и брекер из металлокорда гарантируют повышенную устойчивость.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Разбрасыватель • Автоцистерна •  
Прицеп

Version	STANDARD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	165 D

## Dimensions US Standard

Usa code	94040476
Section Width (inch)	24.1
Overall Diameter (inch)	52.5
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	160.6
Rim Rec	AG 20.00
ECE	E4-106R-001414

## Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3320	3840	4340	5280	6110	7030	7970	8590	9510	10340
40	3640	4210	4770	5800	6700	7730	8750	9420	10450	11350
30	4410	5090	5780	7010	8110	9350	10590	11420	12650	13750
25	4950	5720	6490	7880	9120	10500	11890	12820	14210	15440
15	5740	6650	7540	9160	10590	12210	13820	14900	16510	17940
5	6550	7570	8590	10430	12060	13900	15740	16960	18800	20440

Printed on 25.04.2024 19:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..