

FL 630 SUPER - Загрузить лист технических данных



Description

FL 630 SUPER — шины высокой проходимости для прицепов, цистерн и разбрасывателей, используемых для работы в поле и на дороге. Стойкая конструкция обеспечивает превосходную тягу и великолепное сцепление даже в поворотах и во время маневров. Усиленный борт и брекер из металлокорда гарантируют повышенную устойчивость.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Разбрасыватель • Автоцистерна •
Прицеп

| SIZE | Version | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---------------|----------|-------|-------------------|--------------------|----------|--------------------------------|-----|------|-----|------|-----|------|-----------------|
| 560/60 R 22.5 | STANDARD | 161 D | | | AG 16.00 | 17.00 ; 20.00 | 543 | 1244 | 549 | 3785 | 600 | TL | E4-106R-000794 |
| 560/60 R 22.5 | STANDARD | 165 D | | | AG 16.00 | 17.00 ; 20.00 | 543 | 1244 | 549 | 3785 | 600 | TL | E11-106R-006945 |
| 580/65 R 22.5 | STANDARD | 166 D | | | AG 18.00 | AG 16.00 ; AG 17.00 ; AG 20.00 | 577 | 1326 | 594 | 4058 | 625 | TL | E4-106R-001416 |
| 580/65 R 22.5 | STANDARD | 174 D | 174 D | 174 D | AG 18.00 | AG 16.00 ; AG 17.00 ; AG 20.00 | 582 | 1326 | 594 | 4058 | 625 | TL | E11-106R-008289 |
| 600/50 R 22.5 | STANDARD | 159 D | | | AG 20.00 | | 611 | 1170 | 518 | 3533 | 550 | TL | E11-106R-005992 |
| 600/55 R 22.5 | STANDARD | 162 D | | | AG 20.00 | | 595 | 1232 | 560 | 3757 | 575 | TL | E11-106R-004759 |
| 600/55 R 26.5 | HD | 177 D | | | AG 20.00 | | 611 | 1333 | 604 | 4104 | 625 | TL | E11-106R-003005 |
| 600/55 R 26.5 | STANDARD | 165 D | | | AG 20.00 | | 611 | 1333 | 606 | 4078 | 625 | TL | E4-106R-001414 |
| 650/55 R 26.5 | HD | 178 D | | | AG 20.00 | | 645 | 1389 | 628 | 4292 | 650 | TL | E11-106R-003006 |
| 650/55 R 26.5 | STANDARD | 169 D | | | AG 20.00 | | 645 | 1389 | 627 | 4258 | 650 | TL | E4-106R-000806 |
| 650/65 R 26.5 | STANDARD | 174 D | | | AG 20.00 | | 645 | 1519 | 684 | 4653 | 725 | TL | E4-106R-001651 |
| 710/50 R 26.5 | STANDARD | 170 D | | | AG 24.00 | AG 20.00 | 727 | 1383 | 626 | 4237 | 650 | TL | E11-106R-003009 |
| 750/45 R 26.5 | STANDARD | 170 D | | | AG 24.00 | | 754 | 1349 | 606 | 4147 | 650 | TL | E4-106R-001652 |
| 750/60 R 26.5 | STANDARD | 180 D | | | AG 24.00 | | 754 | 1574 | 694 | 4800 | 725 | TL | E4-106R-001427 |
| 650/65 R 30.5 | STANDARD | 176 D | | | AG 20.00 | | 645 | 1621 | 734 | 4976 | 775 | TL | E4-106R-001653 |
| 750/60 R 30.5 | STANDARD | 181 D | | | AG 24.00 | | 754 | 1675 | 746 | 5115 | 800 | TL | E4-106R-001499 |
| 850/50 R 30.5 | STANDARD | 182 D | 182 D | 182 D | AG 28.00 | | 860 | 1625 | 722 | 4895 | 775 | TL | E11-106R-008232 |

Printed on 25.04.2024 22:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..