FL 633 PERFORMA - Технические спецификации

Description

Новые полностью стальные шины FL 633 PERFORMA прекрасно подходят для нескольких сельскохозяйственных работ, учитывая растущую потребность в логистике. Шины FL 633 PERFORMA, специально разработанные для сельскохозяйственных грузовых автомобилей, представляют собой инновационное решение, улучшающее характеристики как тракторов, так и грузовых автомобилей, а также удовлетворяющее особые потребности современного фермерского хозяйства. Благодаря очень прочному каркасу, превосходной грузоподъемности и выдающейся прочности шины FL 633 PERFORMA являются примером нового уровня шин высокой проходимости, идеально подходящих для разных работ в поле и даже для поездок по шоссе со скоростью до 100 км/ч.

UM

US Standard

Construction

RADIAL

Machinery

Сельское хозяйство: сельскохозяйственный грузовик

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions US Standard

Usa code	94063581
Overall Width (inch)	23.2
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	140.1
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load capacity (lbs)

mph / psi	94
62	11000

Printed on 25.04.2024 3:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..