

FL 637 - Технические спецификации



Description

FL 637 — это радиальные шины высокой проходимости, подходящие для разбрасывателей, прицепов и цистерн. Конструкция усиленных бортов обеспечивает повышенную прочность и увеличенную грузоподъемность. Кроме превосходной проходимости, приводящей к снижению уплотнения почвы, эти шины демонстрируют превосходную способность к самоочищению. Направленный рисунок протектора обеспечивает превосходную тягу и позволяет развивать скорость до 70 км/ч.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Разбрасыватель • Автоцистерна •
Прицеп

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 520/50 R 17 |
| LI/SS | 151D/148E |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 516 |
| Overall Diameter (mm) | 952 |
| Static Loaded Radius (mm) | 414 |
| Rolling Circumference (mm) | 2930 |
| SRI (mm) | 450 |
| Rim Rec | 16.00 |
| ECE | E11-106R-004070 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 915 | 1170 | 1420 | 1610 | 1860 | 2115 | 2335 | 2555 | 2805 | 3150 |
| 65 | 1005 | 1280 | 1555 | 1760 | 2040 | 2315 | 2555 | 2795 | 3075 | 3450 |
| 50 | 1215 | 1545 | 1880 | 2130 | 2465 | 2800 | 3090 | 3385 | 3720 | 4175 |
| 40 | 1365 | 1740 | 2115 | 2395 | 2775 | 3150 | 3475 | 3805 | 4180 | 4695 |
| 30 | 1515 | 1930 | 2345 | 2660 | 3075 | 3495 | 3860 | 4225 | 4640 | 5210 |
| 25 | 1585 | 2020 | 2455 | 2785 | 3220 | 3655 | 4040 | 4420 | 4855 | 5455 |
| 10 | 1805 | 2300 | 2795 | 3170 | 3665 | 4165 | 4600 | 5035 | 5530 | 6210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 04.10.2024 1:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..