

FLOTATION 351 - Технические спецификации



Description

FLOTATION 351 — это диагональные шины высокой проходимости, которые оптимально используются для прицепов. Очень высокие грунтозацепы обеспечивают невероятные тяговые характеристики и долгий срок службы шин. FLOTATION 351 — это идеальные шины для движения на мокрых и влажных поверхностях, обеспечивающие высокую грузоподъемность.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	66 X 43.00 - 25
LI/SS	170 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	1020
Overall Diameter (mm)	1750
Static Loaded Radius (mm)	782
Rolling Circumference (mm)	5213
Rim Rec	36.0 TH
ECE	E11-106R-003346
TRA Code	HF3

Load capacity (Kg)

km/h / bar	2.80
50	6000

Printed on 19.04.2024 3:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..