

FLOTATION 558 - Технические спецификации



Description

FLOTATION 558 — это диагональные шины высокой проходимости, которые подходят для сенокосилок/пресс-подборщиков, автоцистерн и прицепов как на дороге, так и на бездорожье. Они покажут наилучшие характеристики там, где необходима хорошая тяга для надлежащей обработки почвы, а также высокая грузоподъемность.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка • Автоцистерна • Прицеп

Version	STANDARD
Type	TL
Tyre Size	400/55 - 22.5
LI/SS DRIVE WHEEL	140 A8/136 B
LI/SS FREE ROLLING	152 A8/148 B

Dimensions US Standard

Usa code	94006250
Ply Rating	16
Section Width (inch)	15.9
Overall Diameter (inch)	40.2
Static Loaded Radius (inch)	17.5
Rolling Circumference (inch)	121.4
Rim Rec	AG 11.75
Rim Alt	12.25 ; 13.00 ; AG 13.00
ECE	E4-106R-002262

Load capacity (lbs)

mph / psi	54	55	58
5 FR	10460	10640	10960
10 FR	9410	9570	9870
20 FR	8370	8510	8760
25 FR	7470	7590	7830
30 FR	6720	6830	6940
5 DW	7370	7480	7720
10 DW	6640	6730	6940
20 DW	5900	5990	6170
25 DW	5270	5350	5510
30 DW	4740	4820	4940

Printed on 27.04.2024 4:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..