

FLOTATION 648 T - Загрузить лист технических данных



Description

Шины FLOTATION 648 T оптимально подходят для сенокосилок, а также для перевозок по полю и по дорогам. Специальный рисунок протектора с превосходной способностью к самоочищению позволяет перевозить очень тяжелые грузы при низком давлении. Данная шина обеспечивает превосходную тягу и долговечность.

UM

US Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Сенокосилка

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/45 - 22.5	STANDARD	94029242	154 A8/150 B	166 A8/162 B	20	AG 16.00		21.7	42.1	18.7	126.1	TL	E4-106R-002046
550/45 - 22.5	STANDARD	94052066	147 A8/144 B	159 A8/156 B	16	AG 16.00		21.7	42.1	18.7	126.1	TL	

Printed on 25.04.2024 8:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..