

FLOTATION 648 - Технические спецификации



Description

Шины FLOTATION 648 особенно подходят для техники, используемой для перевозок по полям и дорогам, а также для разбрасывателей. Некоторые размерности разработаны для сенокосилок/сеновязалок. Особый рисунок протектора позволяет перевозить большие грузы, оказывая низкое давление на поверхность земли, что снижает уплотнение почвы и предотвращает повреждение культур.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Разбрасыватель

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/45 - 22.5 |
| LI/SS DRIVE WHEEL | 147 A8/144 B |
| LI/SS FREE ROLLING | 159 A8/156 B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 16 |
| Section Width (mm) | 525 |
| Overall Diameter (mm) | 1070 |
| Static Loaded Radius (mm) | 488 |
| Rolling Circumference (mm) | 3253 |
| Rim Rec | AG 16.00 |
| ECE | E4-106R-002309 |

Load capacity (Kg)

| km/h / bar | 2.40 | 2.60 | 2.80 |
|------------|------|------|------|
| 10 FR | 5600 | 5865 | 6125 |
| 20 FR | 5040 | 5280 | 5515 |
| 30 FR | 4480 | 4695 | 4900 |
| 40 FR | 4000 | 4190 | 4375 |
| 50 FR | 3600 | 3770 | 4000 |
| 10 DW | 3935 | 4125 | 4305 |
| 20 DW | 3540 | 3710 | 3875 |
| 30 DW | 3145 | 3300 | 3445 |
| 40 DW | 2810 | 2945 | 3075 |
| 50 DW | 2530 | 2650 | 2800 |

Printed on 19.04.2024 20:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..